

W319ST

Bright and compact short throw projector



- **Bright WXGA projector – 4000 ANSI lumens**
- **Short throw lens - 100" image from just over a metre away**
- **Ultimate control - Crestron, Extron, AMX, PJ-link and telnet LAN commands**
- **Easy connectivity – HDMI, VGA, USB power and 10W speaker**

Project bright vibrant presentations effortlessly any time of day. Designed for small meeting rooms and classrooms, this short throw projector boasts Amazing colour, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

Multiple inputs, USB power and a built-in speaker provide an easy set-up - perfect for connecting to laptop, PC or Blu-ray player for clear projected images with sound. You can even connect a HDMI dongle for wireless presentations.

For ultimate control, the projector comes with RJ45, allowing you to monitor and control your network in multiple rooms.

Specifications

Display/imagen	
Tecnología de visualización	DLP™
Resolución	WXGA (1280x800)
Brillo	4,000 lumens
Ratio de contraste	25,000:1
Relación de aspecto nativo	16:10
Ratio de aspecto - compatible	4:3,16:9
Corrección Keystone-Vertical	+/-40°
Frecuencia de muestreo horizontal	15.38 ~ 91.15Khz
Frecuencia de muestreo vertical	50 ~ 85(120 for 3D)Hz
Uniformidad	75%
Tamaño de pantalla	35.64" ~ 302.98" diagonal
Info Lámpara	
Fuente de luz	Lámpara
Vatios lámpara	203
Vida de lámpara (horas)	6000 (Brillante), 12000 (Dinámica), 10000 (Eco), 15000 (Eco+)
Óptica	
Distancia de tiro	0.52:1
Distancia de proyección (m)	15.75" - 133.86"
Distancia focal (mm)	7.51mm/0.296"
Offset nativo	112%
Conectividad	
Conexiones	Entradas 1 x HDMI 1.4a / 3D + MHL, 1 x HDMI 1.4a / 3D , 2 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x Audio 3.5mm, 1 x Mic 3.5mm Salidas 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm Control 1 x USB-A power 1A, 1 x RS232, 1 x RJ45
General	
Nivel sonoro (típico)	26dB
Nivel sonoro (max)	28dB
Compatibilidad PC	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilidad 2D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
Compatibilidad 3D	Full 3D
Seguridad	Barra de seguridad, Kensington Lock, Interfaz protegida por contraseña
idiomas OSD / display	25 idiomas: Árabe, Checo, Danés, Holandés, Inglés, Farsi, Finlandés, Francés, Alemán, Griego, Húngaro, Indonesio, Italiano, Japonés, Noruego, Polaco, Portugués, Rumano, Ruso, Chino (simplificado), Español, Sueco, Chino (tradicional), Turco, Vietnamita
Condiciones de funcionamiento	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Control remoto	Mando a distancia con láser y función ratón
Altavoces	1
Wattios por altavoz	10W
Contenido de la caja	AC power cord Remote control 2x AA batteries Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Networking	
LAN - control	Yes
Corriente	
Fuente de alimentación	100 ~ 240V, 50 ~ 60Hz
Consumo energético (standby)	0.5W
Consumo energético (min.)	187W
Consumo energético (máx.)	225W
Peso y dimensiones	
Dimensiones (W x D x H)	12.44" x 9.61" x 4.25"
Gross weight	8.66 lbs
Net weight	7.36 lbs

