

ZU720TST

World's first short throw 7000 lumen fixed lens laser projector



- **7000 lumen short throw fixed lens - Ultra bright 0.75~0.95:1 throw ratio for immersive installations**
- **Full motorised lens shift - Ideal for a simple set up**
- **Large zoom range - Motorised zoom expands placement opportunities**
- **Laser light source - Delivers 30,000 hours of virtually maintenance-free operation**

The ZU720TST is the world's first fixed lens 7000 lumen WUXGA short throw laser projector.

At 7000 lumens with 4K and HDR compatibility, the ZU720TST features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include a motorised zoom and 0.75~0.95 throw ratio, full motorised lens shift and built-in dual 10W speakers.

High brightness, colour precision and quiet operation, along with a short throw lens make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as short throw digital signage, edge-blending and projection mapping, simulation, and immersive installations.

The added control flexibility of HDBaseT and LAN make this projector an affordable install and forget solution.

Specifications

Display/imagen	
Tecnología de visualización	DLP™
Resolución	WUXGA (1920x1200)
Brillo	7,000 lumens
Ratio de contraste - dinámico	1,000,000:1
Ratio de contraste - on/off	1,100:1
Relación de aspecto nativo	16:10
Ratio de aspecto - compatible	4:3,16:9
Corrección Keystone - Horizontal	+/-30°
Corrección Keystone-Vertical	+/-30°
Tamaño de pantalla	50" ~ 300" diagonal
Info Lámpara	
Fuente de luz	DuraCore Laser
Vida del LÁSER	30,000horas
Óptica	
Distancia de tiro	0.75:1 ~ 0.95:1
Distancia de proyección (m)	31.89" - 241.34"
Zoom	1.26
Tipo de zoom	Motorizado
Distancia focal (mm)	11.11~14.16
Lens shift	Vertical: +/-50%, Horizontal: +/-15%
Lens shift	Sí - {{downloads_link}}
Conectividad	
Conexiones	<p>Entradas 1 x HDMI 1.4a / 3D , 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync</p> <p>Salidas 1 x HDMI 1.4a / 3D , 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A</p> <p>Control 1 x 12V trigger, 1 x USB-B servicio, 1 x RJ45, 1 x Remoto por cable, 1 x RS232</p>
General	
Nivel sonoro (típico)	27dB
Nivel sonoro (max)	29dB
Seguridad	Barra de seguridad, Kensington Lock, Interfaz protegida por contraseña
Clasificación IP	IP5x
idiomas OSD / display	23 idiomas: Árabe, Checo, Danés, Holandés, Inglés, Farsi, Francés, Alemán, Griego, Indonesio, Italiano, Japonés, Noruego, Polaco, Portugués, Rumano, Ruso, Chino (simplificado), Español, Sueco, Chino (tradicional), Turco, Vietnamita
Operatividad 24/7	Sí
Operatividad 360°	Sí
Condiciones de funcionamiento	10% to 85% Humidity, non-condensing
Control remoto	Mando ProAV retroiluminado
Disipación de calor	1,790BTU/hour
Altavoces	2
Wattios por altavoz	10W
Networking	
LAN	Sí
Corriente	
Consumo energético (standby)	0.5W
Consumo energético (mín.)	320W
Consumo energético (máx.)	510W
Peso y dimensiones	
Dimensiones (W x D x H)	19.06" x 14.8" x 7.03"
Gross weight	36.38 lbs
Net weight	28.44 lbs

