

# UHD50X

Next-Level 1080p Gaming & 4K UHD Home Theater



- **Bright 3,400 lumens with 500,000:1 contrast ratio for lights-on viewing**
- **Ultra-fast 240 Hz refresh rate for unmatched 1080p gaming smoothness**
- **Enhanced Gaming Mode delivers 16ms response time at 1080p, 240 Hz**
- **Vertical lens shift with 1.3x zoom**



Supercharge your huge-screen experience with the 3,400 lumens, 4K UHD Optoma UHD50X projector. Engineered for movies and gaming, the UHD50X delivers incredible details and vibrant colors that brings the cinematic experience home.

## Specifications

<b>Display/image</b>	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	3,400 lumens
Contrast ratio	500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	80%
Screen size	34.1" ~ 302.4" diagonal
<b>Lamp info</b>	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
<b>Optical</b>	
Throw ratio	1.21:1 ~ 1.59:1
Projection distance	47.24" - 318.9"
Zoom	1.3
Zoom type	Manual
Focal length (mm)	12.81 mm~16.74mm/0.504"~0.659"
Lens shift	Vertical +10%
Native offset	105%
<b>Connectivity</b>	
Connections	<p><b>Inputs</b> 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm</p> <p><b>Outputs</b> 1 x Audio 3.5mm, 1 x S/PDIF</p> <p><b>Control</b> 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RS232, 1 x 12V trigger</p>
<b>General</b>	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit home remote
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Input lag	15.70ms
<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	220W
Power consumption (max)	305W
<b>Weight and dimensions</b>	
Dimensions (W x D x H)	12.4" x 10.63" x 4.65"
Gross weight	11.24 lbs
Net weight	8.6 lbs

